

Using R as a GIS

Textbook: Chapter 5

https://ceiba.ntu.edu.tw/1092Geog2017_

授課教師：溫在弘
E-mail: wenthung@ntu.edu.tw

機率與統計 複習測驗

- 某個 1 萬人的城鎮有一家急診醫院，根據歷年統計平均該院每天需接收 8 位急診病患，該醫院共有 20 張急診病床，假設急診病患當日即能出院，且每天病患就診皆為獨立事件。
- 請問：該院在某天出現急診病床不足的機率？

$$f(k, n, p) = \Pr(X = k) = \binom{n}{k} p^k (1 - p)^{n-k}$$

對於 $k = 0, 1, 2, \dots, n$ ，其中 $\binom{n}{k} = \frac{n!}{k!(n - k)!}$

$$P(X = k) = \frac{e^{-\lambda} \lambda^k}{k!}$$

prob = 8/10000

n = 10000

x = 20

pbinom(x, n, prob)

ppois(20, 8)

Contents

- Chapter 5: Using R as a GIS
 - 1. Spatial Intersection
 - 2. Buffering & Merging Spatial Features
 - 3. Data Join
 - 4. Point-in-Polygon and Area Calculations
 - 5. Distance Analysis

R Examples for Geo-processing


- Task 1.1: Tornado damage assessment (Intersection)
- Task 1.2: Creating a tornado density map (Intersection)
- Task 2: Creating service areas (Buffer Zone)
- Task 3.1: Identifying service areas (Distance Analysis)
- Task 3.2: Geographical accessibility (Distance Analysis)

Introducing R functions for spatial analysis


- Spatial Intersection: `st_intersection()`
- Buffering: `st_buffer()`
- Merging Spatial Features: `st_union()`
- Data Join: `left_join()` [dplyr套件]
- Area Calculation: `st_area()`
- Distance Matrix: `st_distance()` + `st_is_within_distance ()`

Spatial Operational Functions in GIS


Spatial Intersection



Buffering




point + polygon



Spatial Operational Functions in GIS

Merging Features (dissolve)



INPUT

OUTPUT

Data Join

GIS layer (shp)

OBJECT ID#	Landuse Code
1	2
2	0
3	1

INPUT

Join Fields


Table (txt)

Landuse Code	Landuse Type
0	Unclassified
1	shrub
2	water

OUTPUT

OBJECT ID#	Landuse Code	Join Table Landuse Code	Join Table Landuse Type
1	2	2	water
2	0	0	Unclassified
3	1	1	shrub

Spatial Intersection: Flooding Risk Analysis



土地利用	面積(平方公尺)	面積百分比 %
工業用地	4,306,266	10.4
水利用地	2,777,436	6.7
交通用地	1,225,045	3.0
建築用地	4,073,363	9.9
軍事用地	197,126	0.5
農業用地	24,841,284	60.1
遊憩用地	575,589	1.4
礦業及土石用地	2,653	0.0
其他用地	3,317,054	8.0
200-Yrs 洪氾區	41,315,816	100.0

	洪水淹沒面積	面積百分比 %
小於5 cm	10,312,488	66.50
5-10 cm	3,889,655	25.08
10-15 cm	1,189,358	7.67
15-26 cm	115,555	0.75
200-Yrs 洪氾區	15,507,056	100.00

Spatial Intersection: Two-way table


土地利用 / 淹水深度	小於5 cm	5-10 cm	10-15 cm	15-26 cm	淹沒面積 (平方公尺)
工業用地	1,644,814	406,837	6,836	0	2,058,487
水利用地	440,763	956,183	841,913	85,017	2,323,876
交通用地	793,649	126,423	27,692	0	947,764
建築用地	2,323,457	797,133	71,197	5,990	3,197,776
軍事用地	77,154	25,713	0	0	102,867
農業用地	3,091,893	818,561	120,144	12,185	4,042,783
遊憩用地	287,854	185,023	32,250	3,366	508,493
礦業及土石用地	780	628	0	0	1,408
其他用地	1,652,125	573,154	89,326	8,997	2,323,602
淹沒面積 (平方公尺)	10,312,488	3,889,655	1,189,358	115,555	15,507,056

Spatial Intersection

Selecting Layer 1 in the Layer 2

Layer 1: tornados (torn)

Layer 2: US States



Selecting tornados in the Area of Interest
(Texas, New Mexico, Oklahoma, Arkansas)

Spatial Intersection

Layer 1: tornados (torn) + Layer 2: US States

Simple feature collection with 6 features and 23 fields

geometry type: POINT

dimension: XY

bbox: xmin: -94.37 ymin: 33.27 xmax: -91.83 ymax: 36.15

CRS: +proj=longlat +ellps=WGS84

	TORNADX020	YEAR	NUM	STATE	MONTH	DAY	DATE	TOR_NO	NO_STS	STATE_TOR	SEGNO	STLAT	STLON	SPLAT	SPLON
2	3	1950	1	05	1	13	1/13/1950	4	1	1	1	34.40	94.37	0.00	0.00
3	4	1950	2	05	2	12	2/12/1950	19	1	1	1	34.48	92.40	0.00	0.00
4	5	1950	3	05	2	12	2/12/1950	23	1	1	1	33.27	92.95	33.35	92.95
5	6	1950	4	05	3	26	3/26/1950	33	1	1	1	34.12	93.07	34.32	92.88
6	7	1950	5	05	3	26	3/26/1950	34	1	1	1	36.15	91.83	36.20	91.75
7	8	1950	6	05	3	26	3/26/1950	35	1	1	1	34.70	92.35	34.80	92.22
	LGTH	WIDTH	FATAL	INJ	DAMAGE	F_SCALE	coords.x1	coords.x2							geometry
2	6	5	1	1	3	3	-94.37	34.40	POINT	(-94.37 34.4)					
3	1	30	0	0	3	2	-92.40	34.48	POINT	(-92.4 34.48)					
4	57	30	0	0	4	2	-92.95	33.27	POINT	(-92.95 33.27)					
5	174	45	0	3	4	2	-93.07	34.12	POINT	(-93.07 34.12)					
6	57	60	0	1	5	3	-91.83	36.15	POINT	(-91.83 36.15)					
7	104	180	0	7	5	2	-92.35	34.70	POINT	(-92.35 34.7)					


預期成果：Spatial Intersection

Task 1.1: Tornado damage assessment (creating a two-way table)


	Arkansas	New Mexico	Oklahoma	Texas
0	563	283	1280	4053
1	23	35	211	378
2	39	33	124	235
3	132	49	376	676
4	235	49	506	919
5	222	25	359	560
6	60	2	92	165
7	15	1	17	36

預期成果：Spatial Intersection

Task 1.2: Creating a tornado density map





Locations of tornados:
point event



Density of tornados
in each state



預期成果：Buffer Zone

Task 2: Creating service areas



預期成果：Distance Analysis



Task 3.1: Identifying service areas



TOTAL_POP	13081
TOTAL_WHITE	8028.00001902

預期成果：Distance Analysis


Task 3.2: Geographical accessibility



Task 1.1: Tornado damage assessment

(creating a two-way table)

1. Mapping
2. Selecting area+ clip
3. Interaction
4. Creating new data frame
5. Crosstab analysis



```
> head(newdf)
```

	Name	Damage
1	Arkansas	3
2	Arkansas	3
3	Arkansas	4
4	Arkansas	4
5	Arkansas	5
6	Arkansas	5

Task 1.1: Tornado damage assessment

2. Selecting area+ clip

```
index <- us_states_sf$STATE_NAME == "Texas" |  
    us_states_sf$STATE_NAME == "New Mexico" |  
    us_states_sf$STATE_NAME == "Oklahoma" |  
    us_states_sf$STATE_NAME == "Arkansas"
```

```
AoI_sf <- us_states_sf [index,]  
AoI_bg <- tm_shape(AoI_sf) + tm_polygons("grey90")
```

```
torn_clip_sf <- torn_sf [AoI_sf, ]
```

```
torn_clip <- tm_shape(torn_clip_sf) + tm_dots(col = "#FB6A4A", size = 0.04,  
                                             shape = 1, alpha = 0.5)  
AoI_bg + torn_clip
```

Task 1.1: Tornado damage assessment

3. Interaction + 4. Creating a new data frame

```
AoI_torn_sf <- st_intersection (AoI_sf, torn_clip_sf)
```

```
AoI_torn_df <- as.data.frame(AoI_torn_sf)
```

```
AoI_torn_df$STATE_NAME <- droplevels(AoI_torn_df$STATE_NAME)  
newdf<- data.frame(Name = AoI_torn_df$STATE_NAME,  
                     Damage= AoI_torn_sf$DAMAGE)
```

Task 1.1: Tornado damage assessment

5. Crosstab analysis

```
> head(newdf)
      Name Damage
1 Arkansas    3
2 Arkansas    3
3 Arkansas    4
4 Arkansas    4
5 Arkansas    5
6 Arkansas    5
```

```
Count <- table (newdf$Damage, newdf>Name)
```

```
Count2 <- xtabs (~ newdf$Damage + newdf$Name )
```

10 min 自行練習 #1

Fast_Food (points) : 台北市速食店分布

Popn_TWN2 (polygons) : 台灣行政區人口數

- 利用 `st_intersection` 計算「台北市大安區」的麥當勞與肯德基的店家數

Task 1.2: Creating a tornado density map

(Counting points in polygons)

```
new1<- st_intersection (us_states_sf, torn_sf)
```

```
df2<- data.frame ( new1$STATE_NAME, new1$TOR_NO)
df3<- table (new1$STATE_NAME)
df3<-as.data.frame(df3)
colnames(df3) <- c("STATE_NAME","Counts")
```



```
us_states_sf<- left_join (us_states_sf, df3) # dplyr package
area1<-st_area(us_states_sf) # unit: foot
```

```
area1<-set_units(area1, km^2) # units package
```

```
us_states_sf$AREA1 <- area1
```

```
us_states_sf$Density <- us_states_sf$Counts / us_states_sf$AREA1
```

```
plot(us_states_sf["Density"], breaks = "jenks", nbreaks = 6, pal=brewer.reds(6))
```



dplyr::left_join()

```
left_join (us_states_sf, df3)
```

sf format

data.frame

	STATE_NAME	Counts
1	Alabama	1266
2	Alaska	0
3	Arizona	196
4	Arkansas	1291
5	California	301
6	Colorado	1631

10 min 自行練習 #2

Fast_Food (points) : 台北市速食店分布

Popn_TWN2 (polygons) : 台灣行政區人口數

- 列出台北市各行政區(名稱)的麥當勞店家總數

Task 2: Creating service areas

```
st_crs(places_sf)
```

```
st_crs(places_sf) <- st_crs(blocks_sf)
```

```
block_bg <- tm_shape(blocks_sf) + tm_polygons("grey90")
```

```
places_pts <- tm_shape(places_sf) + tm_dots(col = "#FB6A4A", size = 0.5)
```

```
block_bg + places_pts
```

```
places_buf_sf <- st_buffer(places_sf, dist = 3000)
```

```
places_buf <- tm_shape(places_buf_sf) + tm_polygons("yellow")
```

```
block_bg + places_buf + places_pts
```

```
places_bufU_sf <- st_union(places_buf_sf)
```

```
places_bufU <- tm_shape(places_bufU_sf) + tm_polygons("yellow")
```


```
block_bg + places_bufU + places_pts
```

10 min 自行練習 #3

Fast_Food (points) : 台北市速食店分布

- 利用 `st_buffer` 建立服務範圍地圖



- 麥當勞店家位置 + 合併的1 km 服務範圍



Task 3.1: Identifying service areas

```
blocks_center_sf <- st_centroid(blocks_sf)  
blocks_center <- tm_shape(blocks_center_sf) + tm_dots(col = "blue")  
blocks_center + places_pts
```

st_distance (blocks_center_sf[1,], places_sf[2,])



Distance matrix

distance.matrix

Units: [US_survey_foot] num [1:129, 1:9]

```
> distance.matrix <- st_distance(blocks_center_sf, places_sf)  
> distance.matrix
```

places (e.g. hospital)

Units: [US_survey_foot]

	[,1]	[,2]	[,3]	[,4]	[,5]	[,6]	[,7]	[,8]	[,9]
[1,]	15368.9406	5448.429	20178.0134	14801.6400	24781.139	21397.9220	29805.861	35214.1327	39097.818
[2,]	14079.7761	2702.521	20341.0506	13859.7754	24610.072	19585.3929	28865.697	34127.9939	37608.631
[3,]	15649.5754	1755.740	22616.3985	15673.7962	26737.346	20592.6104	30545.088	35681.6991	38818.176
[4,]	15440.8047	1298.718	22890.8965	15611.5919	26862.796	20072.1415	30345.024	35399.5893	38351.857
[5,]	16765.4483	3179.382	24752.1461	17133.6300	28561.889	20832.3188	31607.456	36521.2749	39144.329
[6,]	20230.5412	28215.109	10033.9304	18353.2333	12308.029	25092.8183	20988.075	25634.8290	32375.471
[7,]	10144.1070	6767.446	15283.5915	9452.4505	19641.656	16527.2210	24443.114	29861.8132	33875.331
[8,]	19903.0765	27110.731	10150.5028	17975.3860	13073.630	25127.2629	21861.148	26687.5699	33345.272
[9,]	10797.2070	8809.865	14126.5185	9703.2707	18796.924	17543.1673	24344.882	29873.2287	34284.147
[10,]	10391.0545	9925.199	13007.6534	9124.2215	17742.623	17255.9078	23519.356	29078.8075	33647.313
[11,]	10693.2968	11074.266	12277.0756	9256.7941	17136.687	17628.4146	23261.811	28853.7237	33612.564
[12,]	16498.5326	23953.083	7200.0902	14557.3282	11017.562	21920.2886	19808.194	24955.9150	31385.416

centroids

```
distance.matrix <- set_units ( distance.matrix, km)
```

Using `apply()` function

```
near_dist<- apply ( distance.matrix, 1, mean)
```

```
near_dist [1]
```

Units: [km]

	[.1]	[.2]	[.3]	[.4]	[.5]	[.6]	[.7]	[.8]	[.9]
[1,]	4.6844625	1.6606846	6.1502708	4.5115489	7.5533061	6.5220997	9.0848447	10.7332891	11.9170387
[2,]	4.2915243	0.8237301	6.1999646	4.2244680	7.5011651	5.9696397	8.7982820	10.4022333	11.4631336
[3,]	4.7700001	0.5351507	6.8934920	4.7773826	8.1495594	6.2766402	9.3101613	10.8758037	11.8318036
[4,]	4.7063667	0.3958501	6.9771592	4.7584227	8.1877967	6.1180010	9.2491818	10.7898164	11.6896694
[5,]	5.1101189	0.9690774	7.5444692	5.2223409	8.7056813	6.3497035	9.6339718	11.1317069	11.9312154
[6,]	6.1662813	8.5999825	3.0583481	5.5940767	3.7514949	7.6483063	6.3971782	7.8135115	9.8680632
[7,]	3.0919300	2.0627218	4.6584480	2.8811127	5.9867886	5.0375070	7.4502760	9.1018989	10.3252214
[8,]	6.0664698	8.2633673	3.0938794	5.4789086	3.9848505	7.6588051	6.6632911	8.1343876	10.1636593
[9,]	3.2909953	2.6852522	4.3057715	2.9575628	5.7293138	5.3471681	7.4203348	9.1053783	10.4498289
[10,]	3.1671998	3.0252066	3.9647407	2.7810683	5.4079623	5.2596112	7.1687139	8.8632382	10.2557214
[11,]	3.2593234	3.3754430	3.7420601	2.8214765	5.2232725	5.3731515	7.0902143	8.7946326	10.2451301

檢索與查詢

```
> near_dist
```

```
[1] 6.979727 6.630460 7.046666 6.985807 7.399809 6.544138 5.621767 6.611958 5.699067 5.543718  
[11] 5.547189 5.801250 5.362223 5.235401 5.144283 5.070403 5.327462 6.851863 5.181627 6.907600  
[21] 4.444680 6.132781 6.436491 4.999766 5.132661 5.929551 6.952638 5.497788 4.837457 5.121482  
[31] 4.685944 6.013989 5.524350 4.552128 4.615325 4.557320 4.505207 5.273496 5.864437 5.031492  
[41] 5.101440 4.535758 4.510927 4.320297 4.767403 4.328288 4.066674 4.516341 5.385336 4.698343  
[51] 4.263219 4.937443 4.365297 5.520851 5.492109 4.490339 4.371281 4.073150 4.647792 4.065616  
[61] 4.146566 4.858720 4.351617 3.914714 4.492461 3.945327 4.289878 4.140602 4.500801 3.934279  
[71] 4.091489 4.882253 3.887926 3.778863 3.777889 4.615707 4.106746 3.929693 4.226380 3.654365  
[81] 3.683979 3.923749 3.933471 3.823874 4.473364 4.132668 3.456322 3.868349 3.997306 4.020446  
[91] 4.579319 3.795259 3.659066 3.563309 3.633051 4.270348 3.486571 3.681511 3.510291 3.531218  
[101] 3.720148 4.121290 3.839815 3.820938 4.008507 3.453293 3.578081 3.380022 3.669181 3.321075  
[111] 3.551878 3.914578 3.833612 3.789689 3.415499 3.479151 3.657364 3.895911 3.913929 3.516730  
[121] 3.664736 3.540499 3.763959 3.722855 3.764110 3.867976 4.006165 4.452278 5.089665
```

```
xid<- which.min (near_dist)
```

到醫院的平均距離最短的 block id = “110”

```
near_dist [xid]
```

block id = “110”的就醫平均距離 = 3.32017

```
blocks_sf [xid,]
```

挑選出該 block

```
blocks_sf$POP1990 [xid]
```

該 block的人口數(POP1990)

Identifying service areas

挑選最近就醫距離小於1公里的地區


```
min_dist<- apply(distance.matrix, 1, min)
```

```
sel_blocks<- min_dist < 3000
```

```
sel_sf <- blocks_sf [sel_blocks, ]
```

```
sel_map <- tm_shape(sel_sf) + tm_polygons("yellow")
```

```
block_bg + sel_map + places_pts
```



另一種方式 : `st_is_within_distance()`

```
d1<- set_units(1, km)
```


```
sel_blocks = st_is_within_distance (blocks_center_sf, places_sf, dist = d1)
```

```
sel_blocks <- lengths(sel_blocks) > 0
```

```
sel_sf <- blocks_sf [sel_blocks,]
```


```
sel_map <- tm_shape(sel_sf) + tm_polygons("yellow")
```

```
block_bg + sel_map + places_pts
```



另一種方式 : `st_is_within_distance()` -- 繼 (挑選特定一間醫院的1公里服務地區)

```
sel_blocks = st_is_within_distance (blocks_center_sf, places_sf[3,] , dist = d1)  
sel_blocks <- lengths (sel_blocks) > 0  
sel_sf <- blocks_sf [sel_blocks,]  
sel_map <- tm_shape(sel_sf) + tm_polygons("yellow")  
block_bg + sel_map + places_pts
```



```
TOTAL_POP <- sum(sel_sf$POP1990)  
TOTAL_WHITE <- sum(sel_sf$POP1990 * (sel_sf$P_WHITE/100) )
```

Task 3.2: Geographical accessibility

	White	Black	Native	Asian	Other
0	17000.001	208499.99907	1399.99957	99.99946	12600.0009
1	267499.999	32099.99909	599.99970	1600.00021	5299.9994
2	32800.000	65999.99976	100.00039	199.99979	500.0000
3	15300.000	114299.99971	699.99987	699.99987	2600.0003

```
> eth.access
```

sel_blocks	White	Black	Native	Asian	Other
FALSE	3526300	2957100	21600	172800	333300
TRUE	3502000	1763700	18600	141800	617800

```
eth<- as.data.frame(blocks_center_sf[,14:18])
```

```
eth<- as.matrix(eth[,1:5])
```

```
eth<- apply(eth, 2, function(x) (x*blocks_center_sf$POP1990))
```

```
colnames(eth)<- c("White","Black","Native","Asian","Other")
```

```
eth.access <- xtabs (eth~sel_blocks)
```


Task 3.2: Geographical accessibility (cont'd)

```
> eth.access
```

sel_blocks	White	Black	Native	Asian	Other
FALSE	3526300	2957100	21600	172800	333300
TRUE	3502000	1763700	18600	141800	617800

```
> eth.access
```

	sel_blocks	Var2	Freq
1	FALSE	White	3526300
2	TRUE	White	3502000
3	FALSE	Black	2957100
4	TRUE	Black	1763700
5	FALSE	Native	21600



```
eth.access <- as.data.frame(eth.access)
colnames(eth.access) <- c("Access","Eth5","Pop")
```

```
library(ggplot2)
ggplot(eth.access) + aes(fill=Access, y=Pop, x=Eth5) +
  geom_bar(position="stack", stat="identity")
```

Review: R functions for spatial analysis

- Spatial Intersection: `st_intersection()`
- Buffering: `st_buffer()`
- Merging Spatial Features: `st_union()`
- Point-in-Polygon: `crosstab` analysis
- Data Join: `left_join()`
- Area Calculation: `st_area()`
- Distance Matrix: `st_distance()` and
`st_is_within_distance()`

本週實習

Fast_Food (points) 台北市速食店位置

Taipei_Vill (polygons) 台北市各里人口數

擷取麥當勞店家位置；

- 以台北市為範圍，麥當勞 **1 km**為服務範圍內所涵蓋的麥當勞分店數，定義為該家麥當勞店家的連鎖密度，請問哪一家麥當勞的連鎖密度最高？繪製在地圖上，並標示該店家名稱。
- 以台北市為範圍，麥當勞 **1 km**為服務範圍。以台北市各里中心點是否在涵蓋該麥當勞的服務範圍，作為判斷該麥當勞是否能服務到該里的標準。請問哪個里可被麥當勞服務的家數最多？繪製在地圖上，並標示該里的位置及可及的麥當勞店家。

繳交期限：本週五（3/19）

本週作業1

Fast_Food (points) 台北市速食店位置

Taipei_Vill (polygons) 台北市各里人口數

- 將實習所定義麥當勞的連鎖密度，建立 $\text{chainstore}(d)$ 的自訂函數，可繪製服務半徑(d) vs. 麥當勞的關係圖表。



繳交期限：下次上課前（3/29）繳交

本週作業2

Fast_Food (points) 台北市速食店位置

Taipei_Vill (polygons) 台北市村里人口數

- 比較 A區(文山+大安+中正)與 B區(信義+南港+松山) 的麥當勞連鎖密度：

利用統計檢定方法，評估 A區的平均每家麥當勞連鎖密度是否顯著高於 B區。(服務半徑(d) = 1.5 km)

(需列出虛無假設與對立假設，並說明檢定的顯著水準)。

繳交期限：下次上課前（3/29）繳交